

CRUDE C4 SPECIFICATION


NO.	PROPERTIES	UNIT	SALES SPEC.	TEST METHODS
1	C ₃ 's	Wt %	< 0.3	ASTM D-2593
2	MA + PD	Wt. %	< 0.35	ASTM D-2593
3	Other C4's	Wt %	< 62	ASTM D-2593
4	1.3 Butadiene	Wt %	> 38	ASTM D-2593
5	C ₅ 's	Wt %	< 2	ASTM D-2593
6	C6's up	Wt %	< 6	ASTM D-2504
7	Ethyl Acetylene + Vinyl Acetylene	Wt %	< 1.5	ASTM D-2593
8	Total Sulphur	Wt ppm	< 5	GC-FPD
9	Water	Wt ppm	< 10	Dew Point Meter
10	Inhibitor	Wt ppm	< 99	Actual Calculation
11	Oxygen in Liquid Phase	Vol ppm	< 1,000	Oxygen Analyzer
12	Oxygen in Gas Phase	Vol ppm	< 1,000	Oxygen Analyzer

Date Effective: 22-01-2010

TCD1 Manager


Busra Irawan ²⁰/₁₁₀


PD1 Manager


Singgih S.

PPD Manager


Christiana Y.

Monomer Sales GM


Ruly Ariawan ^{22/01/2010}